

INDEX

A

Abrasion	2-9,10,22
Advanced cable dynamics	9-27
Analysis	
Shipboard	7-13,14
Engineering	7-13,14
Aramid fibers	3-7
Coax	4-4
Contra-helical	2-65
Lay length	2-46,47,48,49
Material	2-63
Short, location	2-128
Tightness	2-43,44
Terminations	5-32,38

B

Bearing pressure, sheaves	2-102,3
Bending	8-15,42
Behavior	8-15,17,18
Strength reduction	8-22,42
Book, cable	2-42
Boom, bobbing	8-27
Braiding	2-28
Braided jacket	3-7
Break strength	1-5, 2-24
vs. diameter	2-127
Broken wires	2-56
Buoyancy, sea water	2-24

C

Cable	
Configuration	8-4,5
Damage	9-2,3
Dynamics	9-27
Identification	7-4,5,6,8
Loads	9-8
Logs	7-3,4,7,8,9
Reeving	8-30,31

Stroke amplitude	8-25
Void fillers	8-33
Winding drums	8-32
Cabling	2-28
Coatings, protective	6-7,20
Lubricants	2-51, 6-3,9,11,18
Galvanizing	1-6, 6-17
Plastic	1-6
Coax	4-4
Scripps	4-4,8,9
UNOLS	4-5,8,9,10
Communications, E.O.	4-13,45
Compressed sleeves	5-3,4,5,21,22
Conductors	
Cabling	2-28
Location, open	2-53
Materials	2-59
N Type, E.O.	4-25
Properties	2-98
Resistance	2-47
Stranding	2-27
Construction	1-3, 2-5
Specification	2-65,66
Stretch	8-7
Contra-helical armor	2-11,64
Controls, winch	10-27,28,29
Core	2-17
Elements of motion	8-20,21
Water blocked	2-18
Corrosion	2-9, 2-22
Atmospheric	6-7,8
Immersion	6-10
Protection	6-5,12
Splash zone	6-6,7
Crushing	2-11
Resistance to	2-11

D

Design	
Cable drying	6-19
Considerations	9-27
Electro optical	4-30,33
Trade offs	4-37

Diameter	
Outside	2-49
Power/strength	4-33
vs. breaking	2-127
Diesel hydraulic	11-12
Documentation	7-3
System	7-3,4,8,9
Double drum winch	11-2,4,5
Drag forces	9-8, 10-19
Drum construction	10-38,40
Drum sleeves	2-37
Dynamic loading	9-4

E

Electric resistance	2-47,100
Electric winch drive	10-21, 11-12,14
Electro-hydraulic	11-12
E.M. cable	2-5
Construction	2-5
Diameter	2-127
Elongation	2-24,92,111,119
Manufacturing	2-27
Properties	2-120
Termination	5-25,31
Water blocked	2-18
Environment, working	2-8,9
Epoxy termination	5-3,4,6,7,31,32
Equipment design	9-27
Equipment handling	9-31,32
Eye splice	3-9
E.M.cable	2-33
E.O. cable	4-39
Wire cable	1-3

F

Failure	
Fatigue data	8-45,46,47,48
Fatigue life	8-25,26,27
Mechanisms	8-36
Reporting	7-13
Fairleads	10-23,30,32
Fault location	2-54,69

Fatigue	
Tension	3-4
Fiber optics	4-3,4,10,25,40
Flexure performance	4-41
Next generation	4-37
Non-linear analysis	4-10
Propagation modes	4-18,19,20
Single mode	4-19
Stress/strain	4-42
Fleige fitting	5-31
Field dressing	6-16,17,19,20
Fish bite	2-10
Fleet angles	1-27
Flexing	2-8,9

G

Galvanizing	1-6,14
Gear ranges	10-9,14,20
Grooved shells	1-25,26
	10-17, 11-12,13,14
Grooves, sheaves	1-25,26, 2-37,38
	8-23,25

H

Handling considerations	9-31,32
Hood splice	3-8,9
Hydraulics, winch drives	10-20,21
	11-12,14
Hydrodynamic resistance	9-9

I

Identification	7-4,5,6,8
Immersed weight	9-8
Inertia loads	9-15
Inspection	2-42,43
Armor tightness	2-44,46,47
Installation, wire	1-13,27
Instrumentation, winch	10-34

Insulation	
EM	2-27,28
Materials	2-59,60,62
Properties	2-104
Inventor record	7-2,3,5

J

Jacketing	3-7,8
Braided	3-8
E.M.	2-29
Materials	2-62
Plastic	3-8

K

Kevlar rope	3-2
Applications	3-9
Materials	3-6
Weight compensation	3-2
Kinking	2-10, 8-36,41,45

L

Lay	
Angle	2-12,13
Direction	2-11,44
Length	2-13,46,47,48,49
Lebus shell, lagging	1-8
Length	2-54,55
Determination	2-101,54,55
Free	3-3
By resistance	2-113
By weight	2-114
Life cycle	2-57
Light propagation	4-14
Load	
Dynamic	9-4,5,6,7,8
vs. elongation	2-119
Reaction/tension	8-5
Snap	9-7,8
Static/quasi static	9-3
Zero	9-6,7
Log books	
Cable	2-42,43
Shore based	7-8

Lubrication	6-2,3,4
Field application	6-18,19,20
Need for	2-51
Relubrication	6-3
Wire rope	1-7

M

Magnetic marking	2-67,73
Manufacturing	
E.M. cable	2-27
Lubricant	6-11
Wire rope	1,-5,7
Materials	
Aramid fibers	3-7
E.M. cable	2-59,60,62,70
Kevlar	3-7
Spectra	3-7
Wire rope	1-3
Mechanical termination	3-19
Microbending	4-20,21,23,24,27,42
Modeling, mathematical	8-48
Modulus, elasticity	1-6,8,28
Motion compensation	8-27,28,30
	9-32,33,34,35
Multi-conductor, short location	2-128

N

Nash Tuck splice	1-18,23
N-conductor	4-25
Non-destructive	1-29

O

Open	
Conductor	2-53
Fault	2-54
Operating stress	4-42
Operational characteristics	8-3
Nomenclature	8-3
Optical fibers	
Light propagation	4-14
Propagation modes	4-18
Physical properties	4-13

P

Payload compensation, Kevlar	3-3
Performance	
Characteristics	2-19
Specification	2-65,66
Physical properties	2-120
Pitch diameter	2-14
Plastic jacket	1-6,28, 3-8
Poured sockets	5-4,5,6,13
Predictive load	9-8
Preform	2-12,13
Pre-stress	2-30,125
Properties	
Conductors	2-98
Corrosion resistance	2-22,106
Insulation	2-104
Physical E.M.	2-120
Physical E.O.	4-13,14
Plow steel	2-105

R

Ram tensioning	8-27,44
Reconditioning, wire	2-69
Records	
Cable log	2-42,43, 7-3
Failure	7-13
Inventory	7-3,5
Re-lubrication	6-3,7,11,18,19
Re-reeling	2-54,55,114
Resistance	
Conductor	2-47
Cooper	2-100
Corrosion	2-106
Fatigue	3-3
Length	2-113
Retirement criteria	8-44,45
E.M. cable	2-55,57
Wire rope	1-23, 8-36
Ropes	
Non-metallic	8-38
Rotation	1-5,6,28, 8-13,14
Rust preventatives	6-13,16,18

S

Services	
E.M.	2-67,69
Fault location	2-54,128
Serving, E.M.	2-28
Sheaves	2-37
Bearing pressure	2-52,102,103
Bend over	3-4,7,10
Cable	8-28,30
Diameter	1-25,26, 2-38
Rope	8-43,44
Wrap angle	8-23,24,25
Shielding	
Materials	2-61
Short location	2-128
Single drum winch	10-8
Single mode fibers	4-19
Sleeved drum	2-37
Slip rings, E.O.	4-40
Smooth drum	1-27, 2-35
Snap load	9-7,19
Specifications	
Elements of	2-107
E.M. cable	2-65,66
Performance	2-108
Wire rope	1-28, 7-4,7
Spectra	3-7,9,11,13, 14-7,8
Splicing	
E.M.	2-69
Mechanical	5-54,56
Nash-Tuck	1-18,23
Principals	2-122
Shim stock	2-125
Spooling	
E.M. cable	2-34
E.O. cable	4-43
Re-reeling	2-54,55
Services	2-68,69
Wire rope	1-8,13
Static load	
Immersed	9-8
Quasi static	9-9
Steady state	9-18
Storage	
Wire	2-33,34

Stranding	2-27,60,107
Strength member	2-5,8,11
Stretch	
Constructional	8-7
Elastic	8-7
Kevlar	3-5,10
Wire rope	1-6
Stress relieving	1-7,15,18
Stroke amplitude	8-25
System documentation	7-3,4,8,9

T

Tensile loads	9-3
Tension	
Cycling	2-9
Elongation	2-92,94
Fatigue	3-4,10
Reaction to	8-5,6
Spooling	2-37
Steady state	9-18
Temperature correction	2-55,100
Terminal velocity	9-14,15,30,31
Terminations	5-1
Mechanical	-25,31,37
Nicopress	5-3,5,6,21
Clips	5-3,4,5,6,7,9,10,13
Eye splice	5-49,54,56
Sockets	5-3,6,13,18,21,24
Swaged	5-4,5,6,7,22,24
Wedge	5-3,4,5,6,12,13,51,54
Testing	
Field	2-42
Lubricants	6-12
Non-destructive	1-29, 2-58
Wet	2-28
Torque balance	
E.M. cable	2-19,115
Kevlar	3-4,10
Ratio equation	2-95
Stainless steel	1-14,28
Stress	8-9
Traction winch	
Efficiency	11-6,7
Power	11-12
Sizing	11-11,12
Theory	11-3

Tread diameter	1-25, 2-37, 8-43
Twist balance	2-21

U

Uses	
Fiber optic	4-25
Record	7-6,9

V

Velocity, terminal	9-14,15,30,31
Virtual mass	9-5,7,16,17,24
Void fillers	8-33

W

Water blocked	2-18
Weight - length determination	2-14
Winch	
Capacities	10-9
Construction	10-38
Documentation	7-11
Double drum	11-2,4,5
Drives	10-20,21,22,24 11-8,10,12,14
Efficiency	11-6
E.O.	4-43,44,45
Single drum	10-3,7,8
Wrap angles	8-23,24,25
Wire rope	
Breaking	1-5,8
Coatings	1-6,24
Construction	1-3,4,28
Modulus of elasticity	1-6,8,28
Preservation	1-6, 6-24,26
Rotation	1-5
Specification	1-28
Stress relief	1-3,6,7,8,28
Torque balance	1-1,13

Y

Yield 0.2%	1-5
------------	-----

Z

Zero load	9-2,3,5,6,7,14,18
-----------	-------------------

