

Summary of Vehicle Configurations





1 a b k	
NSIP A	
-12-24	



L×W×H	5m x 3m x 1m (AUV) 5m x 3m x 2.5m (ROV)
Air Weight	2100 kg
Payload	25 kg
Battery	Rechargeable Lithium Ion. 16 kWH
Speed	3 knots (1.5 m/s), 2 knots (1.0 m/s) with work package
Arm	Hydraulic, 7 DOF, 20kg lift at 1m
Thrusters	2 aft, 2 vertical, 1 lateral (ROV)
Lights	Variable output LED arrays for both AUV and ROV modes.
Sonar	Scanning sonar, multibeam (6km max depth), DVL
Sensors	Magnetometer, CTD Flexible interface for additional sensors



DESSC December 2005

Status Report

- Dynamic Model of the vehicle complete with the results being incorporated into the final physical layout.
- All ceramic pressure cases have been successfully delivered and are awaiting final assembly and pressure test.
- Ceramic floatation sphere production on schedule with delivery of complete order expected early in '06
- Manipulator selection complete with workspace design underway
- Prototype microfiber tether canister completed with testing planned using ABE in December
- Deep fiber trials (6000M) planned for April near Guam
- Control computer hardware selection/evaluation underway
- Lithium Ion battery packs on order
- Prototype Light Emitting Diode array and components tested on Jason
- Initial Seatrials pending 2007 ship schedules








DESSC December 2005

Ceramic Components



- First delivery of floatation
 spheres received after
 successful pressure certification
 and acoustic emissions test.
- Main housings received
- Prototype utility housing will be in pressure test end of February












Dynamic Modeling



This plot shows the horizontal vehicle track for two sternplane deflections and offset descent weight.



EANOG



DESSC

December 2005

Manipulation and Workspace

