Replacement Human Occupied Vehicle

Alvin Upgrade



UNOLS Council March, 2014

Brian Midson



















Alvin Upgrade Goals

Phase 1 (4500m)

- Larger personnel sphere; more interior space and improved ergonomics.
- Improved field of view for pilots and observers
- Automated position keeping
- Sampling basket load limits significantly increased
- Improved lighting and video systems
- Improved interior electronics

Phase 2 (6500m)

- ✓ Increased battery capacity
- ✓ Increased on-bottom time
- Increased hydraulic plant capacity (improved manipulator performance)
- Increased thruster horsepower (better maneuverability)
- Improved mid-water research capability

New System Designs

- Personnel sphere (6,500m)
- Penetrators (6,500m)
- Syntactic foam (6,500m)
- Forward frame section
- Pressure vessels (6,500m)
- Video and lighting system
- Command & Control
- Electrical system

Cross-Deck Systems

- -Mercury trim
- Variable ballast
- -Main hydraulics
- -Main ballast
- -Main batteries
- Instrumentation
- Propulsion

Next Steps

- Science Verification Cruise
 Florida Escarpment, 2 legs
- 7 NSF-funded cruises in 2014, (184 days)
 Gulf of Mexico
 EPR, 9N
 Dorado Outcrop
- 4500m Certification
 December, Costa Rica

Phase II

6500m Certification requires:

- Technology Development Batteries!
- Science Pressure
 Community input proposals and/or recommendations
- Funding
 Incremental systems upgrades
 Overhaul

